

## NDS、NDL

### 尼龍紮線帶

### Nylon Cable Tie



#### 廣泛地應用於：

適用各行各業，包括電子、家電、農業、園藝、包裝、玩具業等，在工業上、一般家電產品之電源線電纜之綑綁及生活用品結紮用都是很常見的。

#### Application：

Widely used for various walks of life, including electronics, home appliances, agriculture, horticulture, packaging, toys, and so forth. In industry, it is quite often to be used on general household appliances product to bundle cable power cord and daily use.

#### 特性：

耐酸鹼，承受力強，不易老化

#### Feature：

Acid resistance, reinforced tensile force, and anti-aging.

工作溫度範圍： -25℃~85℃

Temperature Range： -25℃~85℃

顏色：黑色、尼龍本色，其他顏色須訂製

Standard colors： Black、Natural， Others will be able to customize.

認證：符合歐盟 ROHS 規範及通過 SGS 認證

Certificate/ Approval： Meet ROHS and SGS standard.

材質：採用 UL 合格之 NYLON6/6 製成，防火等級 94V-2

Material： UL Approved Nylon (PA)6/6

# NDS、NDL

## 尼龍紮線帶規格

### Nylon Cable Tie Specifications

編號 No.	產品規格 Product Specifications	寬度 Width (m/m)	長度 Length		最大 束線徑 The maximum beam diameter	拉力 Min Loop Tensile Strength		包裝 Package PCS/CTN	淨重 N.W. [KGS]	毛重 G.W. [KGS]	材積 CUFT
			mm	inch		Kgs	Lbs				
1	A-24080	2.4	80	3-3/20	15	8	17-5/8	100,000	22	24	3
2	A-24090	2.4	90	3-1/2	16	8	17-5/8	100,000	24	26	3
3	A-25100	2.5	100	4	18	8.1	18	100,000	27.5	29.5	3
4	A-25120	2.5	120	4-3/4	30	8.1	18	80000	28.5	30.5	3
5	A-25140	2.5	140	5-1/2	35	8.1	18	70000	30	32	3
6	A-25160	2.5	160	6-5/16	40	8.1	18	60000	28.7	30.7	3
7	A-25200	2.5	200	7-7/8	50	8.1	18	50000	29	31	2.6
8	A-36150	3.6	150	5-9/10	33	18.2	40	40000	27	29	2.6
9	A-36200	3.6	200	7-7/8	50	18.2	40	28000	25	27	2.6
10	A-36250	3.6	250	9-7/8	60	18.2	40	22000	28.5	30.5	2.6
11	A-36300	3.6	300	11-3/5	76	18.2	40	20000	30	32	2.6
12	A-36370	3.6	370	14-1/2	102	18.2	40	17000	29.5	31.5	2.6
13	A-48120	4.8	120	4-3/4	24	22.17	50	30000	26.2	28.2	3
14	A-48160	4.8	160	6-5/16	38	22.17	50	20000	23.2	25.2	2.6
15	A-48190	4.8	190	7-1/2	43	22.17	50	20000	26.2	28.2	3
16	A-48200	4.8	200	7-7/8	50	22.17	50	20000	27.6	29.6	3
17	A-48250	4.8	250	9-7/8	60	22.17	50	15000	26.5	28.5	2.6
18	A-48300	4.8	300	11-4/5	76	22.17	50	12000	25.5	27.5	2.6
19	A-48368	4.8	368	14-1/2	102	22.17	50	10000	26	28	2.6
20	A-48432	4.8	432	16-9/10	110	22.17	50	10000	29.5	31.5	3
21	A-76150	7.6	150	5-9/10	36	54.4	120	8000	25.6	27.6	2.6
22	A-76200	7.6	200	7-7/8	50	54.4	120	8000	26.5	28.5	2.6
23	A-76250	7.6	250	9-7/8	65	54.4	120	7000	26	28	2.6
24	A-76300	7.6	300	11-4/5	76	54.4	120	6000	28	30	2.6
25	A-76368	7.6	368	14-1/2	102	54.4	120	5000	28.9	30.9	2.6
26	A-76430	7.6	430	16-9/10	110	54.4	120	4200	26.2	28.2	2.6
27	A-76470	7.6	470	18-1/2	120	54.4	120	5000	36	38	3
28	A-76533	7.6	533	21	140	54.4	120	4000	30.5	32.5	3
29	A-76710	7.6	710	28	190	54.4	120	3000	26.3	28.3	3
30	A-90430	9.0	430	16-9/10	110	79.4	175	3000	27.4	29.4	2.6
31	A-90533	9.0	533	21	140	79.4	175	3000	34	36	3
32	A-90660	9.0	660	26-1/2	175	79.4	175	2500	34	36	3
33	A-90710	9.0	710	28	190	79.4	175	2000	28.2	30.2	3
34	A-90780	9.0	780	30-5/8	228	79.4	175	2000	30.2	32.2	4
35	A-90812	9.0	812	32	239	79.4	175	2000	33.8	35.8	4